



Description

Joint for creating variable angle level changes in insulating material. Of 60 mm height. Grey RAL 7035 colour for easily and quickly creating changes of planes with variable angles.

Advantages

Angulo variable de -90° a +90°

CE conformity to directive 2014/35 / EU.

Material aislante, seguridad eléctrica y reducción de costes en mantenimiento.

Thanks to the articulation it allows the creation of level changes.

Utilizar con kit tornillo aislante DIN603 M8 Metatray. Ref 81000298.

Applications

Solutions



Product data			
Colour		Grey RAL 7035	
Material			PVC
Flange (mm)		60	
Working temperature range (°C)			-20 / 60 °C
kg/u		0.105	
Fire resistance			GRADO UL94: V0
u		12	
UV Behaviour			ULf1 Resistant

Protection System
CU - Copper electroplated
PG - Pregalvanised
EZ - Electrogalvanised
BC - Electrogalvanised Bichromate
BK8 - High Resistance Coating
GC - Hot Dip Galvanising
INOX - Stainless Steel
PT - Polyester Paint
AL - Aluminum
LN - Brass or Nickel-plated brass

Insulating materials
PC+ABS - Halogen Free Polycarbonate + ABS
PVC - Polyvinyl Chloride
PP - Halogen Free Polypropylene
PA6 - Halogen Free Polyamide 6
PA12 - Halogen Free Polyamide 12
PU - Polyurethane
PE - Polyethylene
NBR - NBR rubber
PET - Thermoplastic Polyester
TPV - Thermoplastic

Product applications

