




Category	Bulkheads
Application	Industrial, Outdoor
Specification	Performance

Panther

Panther CCT Wallpack Photocell

Code: APANLED/PC



PRODUCT FEATURES

- Durable compact wall mounted luminaire for general accent illumination and suitable for industrial applications
- Multiple conduit entry and BESA box fixing points
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- All polycarbonate construction ideal for coastal and adverse weather applications
- Selectable CCT between 3000K, 4000K and 6500K output
- Photocell and sensor options

GENERAL INFORMATION

Wattage	25W
Lumens Delivered	2300lm (4000K)
Lm/W	91lm/W (4000K)
Beam Angle	80
CRI	80
CCT	3000/4000/6500K
Input	220-240V
Operating Temp	-10°C - 40°C
SDCM	6
Product Weight without Packaging	1.04 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Wall
Lumen Depreciation	L80 60,000h
Warranty (Years)	3
CE Mark	Yes
Height	305 mm



Category	Bulkheads
Application	Industrial, Outdoor
Specification	Performance

Panther

Panther CCT Wallpack Photocell

Code: APANLED/PC

