Data sheet LED88N

Light / LED Bulkheads

LED88N

6.5W LED Energy Saver Bulkhead Light

Features & Benefits

- Powerful 6.5W LED energy saving bulkhead light
- Ideal for both indoor and outdoor installation
- Colour temperature: 4000K
- Simple and quick to fit with fast-fix terminal block connection



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to +40°C
Ingress Protection Rating	IP55
Wattage	6.5
Beam Angle	90° x 90°
Energy Efficiency	Class G
Energy Usage	6.5KwH/1000H
Lumen Output (Im)	500
Luminaire Efficiency	77 lm/W
Colour Temperature (K)	4000
LED Type	SMD (Integrated)



Subject to technical changes and revisions

additional information at: https://www.timeguard.com This data was generated on

Data sheet **LED88N**

Mounting Hole Centres (mm)	60
Multiple Unit Support	Yes
Cable Capacity (mm2)	2.5mm ²
Cable Entry(s)	Back Entry

General

Weight (g)	300
Height (mm)	205
Width (mm)	108
Depth (mm)	63.5
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings
EAN Number	5012483015094
Guarantee Period	3 Years
Trade Tariff Commodity Code	9405114090

Line Diagrams



