




Features:

- Economical power supply for standard applications
- Natural convection cooling when horizontally mounted
- Encapsulated for use in control cabinets
- Fast and tool-free termination via lever-actuated terminal blocks with push-in connection technology
- DC OK signal output
- Parallel operation
- Electrically isolated output voltage (SELV) per EN 60950-1/UL 60950-1; PELV per EN 60204-1

Technical data

Input		Output	
Phases	2 / 3	Nominal output voltage $U_{o\,nom}$	DC 24 V (SELV)
Nominal input voltage $U_{i\,nom}$	(2 / 3) x AC 400 ... 480 V	Output voltage range	DC 22 ... 28 V (adjustable)
Input voltage range	(2 / 3) x AC 325 ... 575 V; DC 560 ... 700 V	Default Setting	DC 24 V
Nominal mains frequency range	47 ... 63 Hz; 0 Hz	Nominal output current $I_{o\,nom}$	20 A (24 VDC)
Input current I_i	$\leq 3 \times 1.2$ A (400 VAC)	Nominal output power	480 W
Discharge current	≤ 3.5 mA	Deviation	≤ 1 %
Inrush current	≤ 30 A (400 VAC)	Residual ripple	≤ 150 mV (peak-to-peak)
Power factor	≥ 0.7 (400 VAC)	Overload behavior	Constant power (in overload range: 1.05 ... 1.4 x $I_{o\,nom}$); Shutdown and automatic restart in the event of a short circuit
Power factor correction (PFC)	Passive		
Mains failure hold-up time	≥ 10 ms (3 x 400 VAC)		

Signaling and communication	
Signaling	1 x DC OK signal output (PhotoMOS as make contact; can be loaded with max. 31.2 V / 100 mA) 1 x LED DC OK (green) 1 x Overload LED (red)

Operation status indicator	Red LED (overload) Green LED (U_o)
----------------------------	---

Efficiency/power losses	
Power loss P_i	≤ 2.15 W (400 VAC; no load); ≤ 42.5 W (400 VAC; nominal load)

Efficiency (typ.)	92 %
-------------------	------

Circuit protection	
Internal fuse	3 x T 3.15 A / 500 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	3 x Circuit breaker ≥ 10 A; Tripping characteristic: B or C



Safety and protection		
Isolation voltage (pri.-sec.)		DC 4.242 kV
Isolation voltage (pri.-PE)		DC 2.2 kV
Isolation voltage (sec.-PE)		DC 0.7 kV
Isolation voltage (sec.-signal)		DC 0.7 kV
Protection class		I
Protection type		IP20; per EN 60529
Resistance to reverse feed		≤ DC 30 V
Overtoltage category		II
Pollution degree		2
Transient suppression (primary)		Varistor
Short-circuit-protected		Yes
Open-circuit-proof		Yes
Parallel operation		Yes
Series operation		2 devices (max.)
MTBF		> 1,800,000 h (per IEC 61709)

Connection data		
Connection type 1		Input/output
Connection technology		Push-in CAGE CLAMP®
WAGO connector		WAGO 2606 Series
Solid conductor		0.5 ... 6 mm² / 20 ... 10 AWG
Fine-stranded conductor		0.5 ... 6 mm² / 20 ... 10 AWG
Strip length		11 ... 13 mm / 0.43 ... 0.51 inches
Connection type 2		Signaling
Connection technology		Push-in CAGE CLAMP®
WAGO connector 2		picoMAX® 3.5 (WAGO 2091 Series)
Solid conductor 2		0.2 ... 1.5 mm² / 24 ... 14 AWG
Fine-stranded conductor 2		0.2 ... 1.5 mm² / 24 ... 14 AWG
Strip length 2		8 ... 9 mm / 0.31 ... 0.35 inches

Physical data		
Width		80 mm / 3.15 inches
Height		130 mm / 5.118 inches
Depth from upper-edge of DIN-rail		170 mm / 6.693 inches

Mechanical data		
Mounting type		DIN-35 rail

Material data		
Fire load		0.197 MJ
Weight		1710 g



Environmental requirements	
Ambient temperature (operation)	-20 ... +70 °C
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	10 ... 95 % (no condensation permissible)
Derating	-2 %/K (> 45 °C)
Climatic category	3K3 (per EN 60721)
Resistance to shock and vibration	Shock: 15g (per EN 60068-2-27) Vibration: 1g (per EN 60068-2-6)

Standards and specifications	
Conformity marking	CE; EAC
Standards/specifications	EN 61204-3 EN 62368-1 cURus 60950-1 cURus 62368-1 cULus 508 CSA C22.2 SEMI F47

Commercial data	
eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 9.0	EC002540
ETIM 8.0	EC002540
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4055143588973
Customs tariff number	85044083900

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

General approvals			Declarations of conformity and manufacturer's declarations		
   					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078	EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081	MFD for SEMI F47 WAGO GmbH & Co. KG	-	-
UL Underwriters Laboratories Inc.	UL 508	E255817	UK-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-
UR Underwriters Laboratories Inc.	UL 60950-1	E255815			
UR Underwriters Laboratories Inc.	UL 62368-1	E255815			



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-2742

Download icon

Documentation

Bid Text

787-2742	13.06.2019	xml 7.42 KB	Download icon
787-2742	13.06.2019	docx 23.18 KB	Download icon

Instruction Leaflet

Primär getaktete Stromversorgung ECO	V 1.5.0	pdf 980.89 KB	Download icon
--------------------------------------	---------	------------------	---------------

CAD/CAE-Data

CAD data

2D/3D Models 787-2742	Download icon
--------------------------	---------------

CAE data

EPLAN Data Portal 787-2742	Download icon
ZUKEN Portal 787-2742	Download icon

1 Compatible Products

1.1 Optional Accessories

1.1.1 Tool

1.1.1.1 Operating tool



[Item No.: 210-719](#)
Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft



[Item No.: 210-769](#)
SCREWDRIVER; green