

Polyester Cabinet 300x250x140

Polyester Cabinet



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| Protection class | IP66 |
|---------------------------|-------------------------------|
| Glow wire test | 850 °C |
| Temp. range min | -25 °C |
| Temp. range max | 85 °C |
| Impact resistance | IK10 |
| Material | Polyester |
| Product Color | RAL 7035 |
| External dimensions LxWxH | 300x250x140mm |
| Туре | Polyester Cabinet 300x250x140 |
| Order no. UK | 50108494 |
| Packing unit | 1 |

Additional Info:

- Empty cabinets made of polyester reinforced with fiberglass
- For use in electrical networks
- For surface mounting
- Insulation: Class II
- With lock
- Optional locks: metal key, triangle, padlock
- Door opening: 180°
- Option to put mounting plate in the enclosure (insulating or metallic)
- External fixing to the wall
- Resistant to chemical and atmospheric agents

Specification to the following: Directive 2014/35/UE Directive 2011/65/UE (RoHS)





Electrical Low Voltage Regulation

In Accordance with EN 62208 and EN 60670-1

Recommended accessories

| Polyester Plate for 300x250x140mm | 50108719 |
|-----------------------------------|----------|
| Metal Plate for 300x250x140mm | 50108724 |

22.05.2024

Other technical data on request / subject to change without notice