

Reference no.	Cable Type
0361	Welding cable, tinned copper conductor, vulcanised rubber insulation / tough rubber sheath. BS 638
2093Y	3-core, thermoplastic heat resisting insulation / thermoplastic heat resisting sheathed. Circular, 300/300 V BS 6500, flexible cord
218*Y	Circular, thermoplastic insulation / thermoplastic sheathed. 300/300 V BS 6500, flexible cord
2192Y	2-core, thermoplastic insulation / thermoplastic sheathed flat 300/300 V BS 6500, flexible cable
2213	3-core, vulcanised rubber insulation/tough rubber sheathed/cotton braid, 300/300 V BS 6500, flexible cord
318*	Circular, vulcanised rubber insulation / tough cord rubber sheathed, 300/500 V BS 6500, flexible cord
318*Y	Circular, thermoplastic insulation / thermoplastic sheathed, 300/500 V BS 6500, flexible cable
318*P	Circular, vulcanised rubber insulation/PCP sheathed, 300/500 V BS 6500, flexible cord
318*TQ	Circular, EPR insulation/CSP sheathed 300/500 V BS 6500, flexible cord
618*Y	Circular, thermoplastic insulation / thermoplastic sheathed 1-35mm ² 300/500 V BS 6004 50-630mm ² gen in acc BS6346, wiring cable
619*Y	Flat, thermoplastic insulation / thermoplastic sheathed 300/500 V BS 6004, wiring cable
624*Y	Flat, thermoplastic insulation - laid up in parallel with a barc CPC within one interstice / thermoplastic sheathed 300/500 V BS 6004, wiring cable
6419X	Single-core, thermoplastic insulation 1 - 630mm ² . 450/750 V BS 6004
657*TQ	Circular, EPR insulation/CSP sheathed 600/1000 V BS 6883, ship- wiring cable. (circular conductors)
657-TQ(S)	As 657*TQ but with shaped conductors
658*TQ	Circular, EPR insulation/CSP bedding/galv. mild steel wire braid amour/CSP sheathed 600/1000 V BS 6883, ship wiring cable (circular conductors)
658-TQ(S)	As 658*X but with shaped conductors
694*X	Circular, thermoplastic insulation / thermoplastic bedded / single steel wire armoured / thermoplastic sheathed 600/1000 V BS 6346, mains wiring cable
649*X(S)	As 694*X but with shaped conductors
H07V-R	Single-core, thermoplastic insulation, 1.5-630mm ² , (rigid strand) 450/750 V to BS 6004
H07V-U	Single-core, thermoplastic insulation, 1.5-2.5mm ² , (solid) 450/750 V to BS 6004
H05V-U	Single-core, thermoplastic insulation, 1.0mm ² (solid) 300/500 V to BS 6004

Reference no.	Cable Type
H05RR-F	Circular, vulcanised rubber insulation/tough rubber sheath 300/500 V to BS 6500
H03VV-F	Circular, thermoplastic insulated / thermoplastic sheathed, 300/300 V to BS 6500
H03VVH2-F	Flat 2-core, thermoplastic insulated / thermoplastic sheathed, 300/300 V to BS 6500
H05VVF-F	Circular, thermoplastic insulated / thermoplastic sheathed, 300/500 V to BS 6500
H05VVH2-F	Flat 2-core, thermoplastic insulated / thermoplastic sheathed, 300/500 V to BS 6500
H05V-K	Single-core, thermoplastic insulation 0.5 - 1.0mm ² 300/500 V to BS 6004
H07V-K	Single-core, thermoplastic insulation, 1.5 - 2.5mm ² , 450/750 V to BS 6004
H07RN-F	Circular, rubber insulated / rubber sheathed, 450/750 V to BS 6007

Notes:

* = number of cores (e.g. 2183Y is 3-core)

(AL) = aluminium conductors. To be added after other suffix, if used, e.g. 6491X(AL) and 6242Y(AL)

(S) = Shaped conductors

(Reproduced with kind permission of Anixter (UK) Ltd).